

STAR 20 PC

(Ref. 20501019)

Dry drilling of metals, plastic materials and wood
Usage d'appoint

Guarantee: 2 ans

Photo et textes non contractuels

Product Information:

Steel cast iron column
V-belt transmission
Spindle fitted on bearings
ON/OFF switch fitted with a lack of voltage coil
Emergency Stop through mushroom stay put button
Safety-grip microswitch around belt cover
Protective shield of servo chuck
Tilting table up to 45 °
Rack-driven table

Supplied with:
- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift
- Screw vice and set of clamps

Technical characteristics:

Height (cm) : 160.00
Width (cm) : 40.00
Length (cm) : 64.00
Net weight (Kg) : 57.40
Power(kW)
Power (V) 1-phase 230V
Spindle speed (rpm)
Max. drilling capacity (mm)
Morse taper MT2
Column dia (mm)
Spindle stroke (mm)
Number of gears
d: spindle/column distance (mm)
e: spindle/base distance (mm)
f: spindle/table distance (mm)
Table dimension (mm)
Lighting No
Servo screen Yes
Reversible vice table No
Coolant No
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping No
Cross motion table No