



Photo et textes non contractuels

## JET 60 iRE

(Ref. 20402050)

Water and dust suction  
**Usage très intensif**

Norm: EN 60335-2-69

Guarantee:  

### Product Information:

"Fitted with an external feeding pump (power 400W, cutting-off 60l/min) with a symmetrical fire hose coupling)

Possible delivery up to max. 7 m

Manual unclogging system of the filter using a single button

Class M cartridge filter

Metal accessories and stainless steel tubes

Aluminium base with large built-in handle

Storage unit of accessories integrated to the base

Large reinforced 2-wheel + 2-castor base for an optimised stability

Anti-crushing shielded hose

Dual-turbine suction

By-pass cooling down system motor designed for heavy-duty jobs (air is sucked by a third turbine on top of the motor, only for cooling down)

Anti-static electricity plate connected to earth

Neoprene power table HO7 RNF length 7 m"

### "Standard accessories:

- Bent tubes 2 x 500 mm Ø 40 mm
- hose Ø 40 mm, length 2.5 m
- Dust nozzle - 400 mm
- liquid nozzle - 400 mm
- round brush
- flat nozzle
- accessory fitting
- Class M cartridge filter PTFE

### Technical characteristics:

Height (cm) : 98.80

Width (cm) : 68.00

Length (cm) : 61.00

Net weight (Kg) : 42.80

Power (W)

Power (V) 1-phase 230V

Tank stainless steel

Tank capacity (l)

Depression (Kpa) 23.52

Flow (l/min) 7 070

Sound level (dBA) 76.5

Atex Zone 22 No

Accessory diameter (mm)

Unclogging Yes

Class-M approved No

Vacuum cleaner filter Class M PET cartridge

Synchro socket No

Cable length (m)

Tank capacity (L)