



## STAR 16 PE

(Ref. 20501017)

Dry drilling of metals, plastic materials and wood  
**Usage d'appoint**

Guarantee:  

Photo et textes non contractuels

### Product Information:

- Steel cast iron column
- V-belt transmission
- Spindle fitted on bearings
- ON/OFF switch fitted with a lack of voltage coil
- Emergency Stop through mushroom stay put button
- Safety-grip microswitch around belt cover
- Protective shield of servo chuck
- Tilting table up to 45 °
- Rack-driven table

### Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift
- Screw vice and set of clamps

### Technical characteristics:

- Height (cm) : 54.00
- Width (cm) : 31.00
- Length (cm) : 85.00
- Net weight (Kg) : 32.60
- Power(kW)
- Power (V) 1-phase 230V
- Spindle speed (rpm)
- Max. drilling capacity (mm)
- Morse taper MT2
- Column dia (mm)
- Spindle stroke (mm)
- Number of gears
- d: spindle/column distance (mm)
- e: spindle/base distance (mm)
- f: spindle/table distance (mm)
- Table dimension (mm)
- Distance between table grooves (mm)
- Lighting No
- Servo screen Yes
- Reversible vice table No
- Coolant No
- Automatic down motion (mm/tr) No
- Slow down motion No
- Semi automatic tapping No
- Cross motion table No