



Photo et textes non contractuels

## 30 CVTE

(Ref. 20502066)

Drilling and tapping of metals, plastic materials and wood, with coolant

**Usage intensif**

Guarantee:  

### Product Information:

Steel cast iron frame, head and stand  
Steel column  
Transmission through Poly V belts with tension adjustment  
Spindle fitted on bearings  
Adjustable spindle rack motion through return spring  
Drilling-depth stop  
Electronic speed variator  
Digital display of the spindle speed  
Controls : Emergency Stop through mushroom stop button, Safety microswitch of the pulley cover, Spindle speed override button  
Servo detachable chuck protective shield  
LED lighting 12 V - 6 W  
2-position reversible vice table, vernier  
Vice fitted on guideways  
Rack-driven table

### Supplied with:

-Self-clamping chuck,  
-Chuck shank,  
-Taper drift

### Technical characteristics:

Height (cm) : 175.00  
Width (cm) : 77.00  
Length (cm) : 65.00  
Net weight (Kg) : 187.90  
Power(kW)  
Power (V) 3-phase 400V  
Spindle speed (rpm)  
Max. drilling capacity (mm)  
Morse taper MT3  
Column dia (mm)  
Spindle stroke (mm)  
Number of gears  
d: spindle/column distance (mm)  
e: spindle/base distance (mm) 1 150  
f: spindle/table distance (mm)  
Table dimension (mm)  
Distance between table grooves (mm)  
Lighting Yes  
Servo screen Yes  
Reversible vice table Yes  
Coolant Yes  
Jaw width (mm)  
Jaw height (mm)  
Opening (mm)  
Automatic down motion (mm/tr) No  
Slow down motion No  
Semi automatic tapping No  
Cross motion table No