



## 25 FV

(Ref. 20502080)

Drilling, tapping, milling metals, plastic materials and wood,  
(coolant is optional)

**Usage intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

- Steel cast iron frame, head and stand
- Dovetail column
- Emergency Stop through mushroom stay put button
- Semi automatic tapping system on handles and instant return
- Left and right tilting milling head
- Slow down motion
- Servo polycarbonate screen
- Cross-motion table, stroke 145 x 400 mm
- Table grooving - distance between centers 45 mm
- Electronic speed variator
- Digital display of the spindle speed et de la profondeur de perçage

### Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- rapid-clamping vice 100 mm
- Without stand

### Technical characteristics:

- Height (cm) : 85.00
- Width (cm) : 73.00
- Length (cm) : 76.00
- Net weight (Kg) : 181.00
- Power(kW)
- Power (V) 1-phase 230V
- Spindle speed (rpm) 100 : 1800
- Max. drilling capacity (mm)
- Max. tapping capacity (mm)
- Milling capacity (mm)
- Morse taper MT3
- Spindle stroke (mm)
- Number of gears
- d: spindle/column distance (mm)
- f: spindle/table distance (mm)
- Table dimension (mm)
- Distance between table grooves (mm)
- Lighting No
- Servo screen Yes
- Reversible vice table No
- Coolant No
- Transversal / longitudinal stroke (mm)
- Automatic down motion (mm/tr) No
- Slow down motion Yes
- Semi automatic tapping Yes
- Cross motion table Yes