



Photo et textes non contractuels

## SR 264 DG DA

(Ref. 20114122)

Usage intensif

Guarantee:  

### Product Information:

- Left and right cutting
- Autonomous down move of the arch
- Very highly rigid steel cast iron arch
- Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band
- Adjustable front mobile band guide
- 2-point lubrication system through electropump
- Vice support tilting with the arch
- Hydraulic vice
- 24V very low voltage controls
- Emergency Stop through mushroom stay put button
- Band cover fitted with a microswitch
- Motor protection through thermal circuit breaker
- Electrical protection IP54
- Coaxial reducer motor

### Supplie with:

- base
- band saw
- adjustable cut stop

### Technical characteristics:

- Height (cm) : 140.00
- Width (cm) : 66.00
- Length (cm) : 140.00
- Net weight (Kg) : 302.00
- Power(kW)
- Power (V) 3-phases 400V
- Speed (m/min)
- Round cutting capacity (mm) at 90°
- Square cutting capacity (mm) at 90°
- Rectangle cutting capacity (mm) at 90°
- Left round cutting capacity (mm) at 45°
- Left square cutting capacity (mm) at 45°
- Left rectangle cutting capacity (mm) at 45°
- Left round cutting capacity (mm) at 60°
- Left square cutting capacity (mm) at 60°
- Left rectangle cutting capacity (mm) at 60°
- Vice opening (mm)
- Working height (mm)
- Tape (mm)
- Right rectangle cutting capacity (mm) at 45°
- Right round cutting capacity (mm) at 45°
- Left square cutting capacity (mm) at 45°