



## EXPERT 250 SR DGDV

(Ref. 20114137)

Dry steel, stainless steel and aluminium sawing with coolant with coolant

**Usage régulier**

Guarantee:  

Photo et textes non contractuels

### Product Information:

- Cuts left and right
- Aircast fram
- Saw blade guides equipped with bearings and carbide pads to ensure excellent resistance to saw blade wear
- Adjustable anterior tape guide
- Autonomous descent by gravity controlled by hydraulic cylinder
- 2-point electro-pump lubrication device
- Safety micro-switch and tension gauge saw blade
- Fast-tightening set mounted on game catch-up slide
- Variable speed saw blade
- Control desk in front
- Very low voltage controls 24 V
- Stopping punch to hook
- Carter saw equipped with a positive micro-reuptor
- Motor protection by heat breaker
- Motor with coaxial gearbox

**Supplied with base, saw blade and 500 mm adjustable cut stop**

### Technical characteristics:

- Height (cm) : 180.00
- Width (cm) : 100.00
- Length (cm) : 185.00
- Net weight (Kg) : 306.00
- Power(kW)
- Power (V) 3-phase 400V
- Speed (m/min)
- Round cutting capacity (mm) at 90°
- Square cutting capacity (mm) at 90°
- Rectangle cutting capacity (mm) at 90°
- Left round cutting capacity (mm) at 45°
- Left square cutting capacity (mm) at 45°
- Left rectangle cutting capacity (mm) at 45°
- Left round cutting capacity (mm) at 60°
- Left square cutting capacity (mm) at 60°
- Left rectangle cutting capacity (mm) at 60°
- Vice opening (mm)
- Working height (mm)
- Tape (mm)
- Right rectangle cutting capacity (mm) at 45°
- Right round cutting capacity (mm) at 45°
- Left square cutting capacity (mm) at 45°