

JET 50 P

(Ref. 20402046)

Water and dust suction
Usage très intensif

Norm: EN 60335-2-69
Guarantee: 3 ans CE

Photo et textes non contractuels

Product Information:

"Manual unclogging system of the filter using a single buTon
Water-resistant high-efficiency 9.9% Class M cartridge filter
Metal accessories and stainless steel tubes
Storage unit of accessories integrated to the base
Large 2-wheel + 2 castors for a stabilised stability
Anti-crushing shielded hose
Dual-turbine suction

By-pass cooling down system motor designed for heavy-duty jobs (air is s ucked by a third turbine on top of the motor, only for cooling down)
Anti-static electricity plate connected to earth
Neoprene power table HO7 RNF length 7 m"

"Standard accessories:
- Bent tubes 2 x 500 mm Ø 40 mm
- hose Ø 40 mm, length 2.5 m
- Dust nozzle - 400 mm
- liquid nozzle - 400 mm
- round brush
- flat nozzle
- round brush fitting
- Class M cartridge filter PTFE

Technical characteristics:

Height (cm) : 92.00
Width (cm) : 52.00
Length (cm) : 63.00
Net weight (Kg) : 27.00
Power (W)
Power (V) 1-phase 230V
Tank Polypropylene
Tank capacity (l)
Depression (Kpa) 23.52
Flow (l/min) 3 600
Sound level (dBA)
Atex Zone 22 No
Accessory diameter (mm)
Unclogging Yes
Class-M approved No
Vacuum cleaner filter Class M PET cartridge
Synchro socket No
Cable length (m)
Tank capacity (L)