



## SPC 32 TC VEL DL T

(Ref. 20601146)

Drilling metals, plastic materials and wood, with coolant  
**Usage très intensif**

Guarantee:  **3** 

Photo et textes non contractuels

### Product Information:

Cross move table  
Electronic speed variator  
Slow down motion  
Semi automatic tapping  
Steel cast iron frame, head and stand  
Steel column  
Machined aluminium pulleys  
Transmission through V belts with rapid adujstment of tension  
Spindle fitted on bearings  
Adjustable spindle mack motion through return spring  
24V very low voltage controls :  
- ON/OFF  
- Switching on lamp  
- Emergency Stop through mushroom stay put button  
- 3-point locking circuit breaker  
Detachable servo protective shield  
24V lighting  
Electrical protection IP54  
Noise level 50 dB  
Rack-driven table, graisseur de la vis sans fin

### Technical characteristics:

Height (cm) : 180.00  
Width (cm) : 43.50  
Length (cm) : 88.00  
Net weight (Kg) : 350.00  
Power(kW)  
Power (V) 3-phase 400V  
Spindle speed (rpm)  
Max. drilling capacity (mm)  
Milling capacity (mm)  
Morse taper MT3  
Column dia (mm)  
Spindle stroke (mm)  
Number of gears  
d: spindle/column distance (mm)  
e: spindle/base distance (mm) 1 210  
f: spindle/table distance (mm)  
Table dimension (mm)  
Distance between table grooves (mm)  
Lighting Yes  
Servo screen Yes

Hot weather adaptation on request  
Can be modified to 230V three-phase on request  
Machined aluminium pulleys

Transversal / longitudinal stroke (mm)  
Automatic down motion (mm/tr) No  
Slow down motion Yes  
Semi automatic tapping Yes  
Cross motion table Yes

**Supplied with Self-clamping chuck and Chuck shank**