



Photo et textes non contractuels

Product Information:

45° tilting head to the left and the right
Rapid clamping vice.
Burr-free double vice
Mobile jaw to perform right 45° cut
Protective cover of detachable saw mill
Lubrication system of saw mill using a pump
Drive through an oil-bath reducer
Steel cast iron frame
Control arm fitted with a trigger switch
Very low voltage controls 24 V
Emergency Stop through a mushroom stay put button
Electronic speed variator
Electrical insulation IP 54

Supplie with:

- base
- Circular saw blade
- 540 mm adjustable cut stop

TS 315V

(Ref. 20114202)

Cutting under lubrication of steel, stainless steel and aluminum

Usage régulier

Guarantee:  

Technical characteristics:

Height (cm) : 183.00
Width (cm) : 99.00
Length (cm) : 102.00
Net weight (Kg) : 178.00
Power(kW) 1.5
Power (V) 3-phases 400V
Rotation speed (rpm) 15-120
Round cutting capacity (mm) at 90° 100
Square cutting capacity (mm) at 90° 82
Rectangle cutting capacity (mm) at 90° 110 x 70
Left round cutting capacity (mm) at 45° 90
Left square cutting capacity (mm) at 45° 80
Left rectangle cutting capacity (mm) at 45° 85 x 70
Vice opening (mm) 120
Working height (mm) 970
Dimension of the blade 315 x 2.5 x 32
Right rectangle cutting capacity (mm) at 45° 85 x 70
Right round cutting capacity (mm) at 45° 90
Left square cutting capacity (mm) at 45° 80
Abrasive disc dimension (mm) 315 x 2.5 x 32