

PRODUCT SHEET | Update File: 5/17/2024 TABLES SAWS |





Usage très intensif

Guarantee: 🚟 🧲

Photo et textes non contractuels

Product Information:

Table saw made entirely of stainless steel, high durability in daily use Site cutting machine very resistant to corrosion and weather t hanks to their stainless steel structure. Extremely durable, robust and accurate. Designed for cutting all decorative materials, tiles, p orcelain stoneware, concrete slab, slabs, stones, marble, granite. High quality motor with large disc clamping flanges Ø 110 mm ens uring maximum rigidity during cutting Machine fitted on a bracket to perform precise cuts of large tiles up to 1200 mm Bearing-cuttin Disk bore (mm) 25.4 g head fitted on guideways with tilting device to perform bevelled cuts (45ø) Adjustable cutting depth Supporting scale with orientab le cutting stop up to 45ø Built for 4 extensions in option for a bette r stability of large tiles Cooling circuit of the blade with wet pump, with flow control valve Independent water pump tray for easy emp tying and cleaning The water tank, made of stainless steel, is fully welded to structural reinforcements that ensure high resistance to torsion and bending. The emptying of the water tank is done by m eans of the removal of the plug Ease of cleaning the water tank th anks to the butterfly opening trays and tool-free disassemblies Fol ding feet to make transport easier Frame fitted with transport whe els to move the device more easily Transport wheels with steel rim on ball bearing Fitted with a lack ot voltage coil Local fabrication in 41

Delivery with diamond blade ULTRA CERAM-E 250

Technical characteristics:

Height (cm) : 130.00 Width (cm) : 58.00 Length (cm) : 201.00 Net weight (Kg): 91.74 Power (W) 1500 Power (V) 1-phase 230V Rotation speed (rpm) 2800 Disk diameter (mm) 250 Length cutting capacity (mm) 90° 1215 Height cutting capacity (mm) 90° 60 Left height cutting capacity (mm) 45° 1215 Left heigth cutting capacity (mm) 45° 40 Water tank (I) 10 Tile thickness (mm) 30 Disc stroke (mm) 1280 Cutting capacity (mm) 90° Height 2 cuts 96