

**25 F HSS 118°**

(Ref. 11500002)

Drilling of low-alloy steels, ferrous metals, aluminium and cast iron  
**Usage intensif**

**Photo et textes non contractuels**

**Product Information:**

Box of 25 HSS metal drills

Split-point grinding: reduction of the drill tip. Enables the easy self-centring of the drill bit on the smoothest of surfaces. Significantly reduces the required axial load.

118° tip: 118° tip angle for the sharpening of the drill bit. Suitable for general uses in long chip materials. Allows a quick attack of the material and easy centering.

Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. Enables versatile use on portable electrical tools and machine tools.

30° type N flute: normal flute profile with a 30° helix angle. Suitable for general use.

Cut-ground drill, more resistance and excellent drilling accuracy.

Provides good rigidity to the tool, as well as excellent drilling precision.

High-speed steel: HSS substrate. For general uses in steel up to 950 N/mm<sup>2</sup>, cast iron and aluminium.

**Technical characteristics:**

Height (cm) : 6.00

Width (cm) : 11.50

Length (cm) : 20.00

Net weight (Kg) : 1.10

For machine Floor machine drill, portable drill

Characteristic 1 Box of drill bits HSS

Diameter (mm)

Shank (mm) Cylindrical