



JET 15 i

(Ref. 20402040)

Water and dust suction

Usage très intensif

Norm: EN 60335-2-69

Guarantee:  

Photo et textes non contractuels

Product Information:

Manual unclogging system of the filter using a single button
 Water-resistant high-efficiency 9.9% Class M cartridge filter
 Metal accessories and stainless steel tubes
 Carbon-fibre reinforced base
 Storage unit of accessories integrated to the base
 Large 2-wheel + 2 castors for a stabilised stability
 Anti-crushing shielded hose
 By-pass cooling down system 1450W motor designed for continuous heavy-duty jobs (air is sucked by a third turbine on top of the motor, only for cooling down)
 Suction, depression and cutting-off high-performance
 Anti-static electricity plate connected to earth
 Neoprene power table HO7 RNF length 7 m

Technical characteristics:

Height (cm) : 60.00
 Width (cm) : 42.50
 Length (cm) : 46.00
 Net weight (Kg) : 13.18
 Repairability index
 Power (W)
 Power (V) 1-phase 230V
 Tank stainless steel
 Tank capacity (l)
 Depression (Kpa) 26.7
 Flow (l/min) 4 200
 Sound level (dBA)
 Atex Zone 22 No
 Accessory diameter (mm)
 Unclogging Yes
 Class-M approved No
 Vacuum cleaner filter Class M PET cartridge
 Synchro socket No
 Cable length (m)
 Tank capacity (L)

Standard accessories:

- Bent tubes 2 x 500 mm Ø 32 mm
- hose Ø 32 mm, length 2,2 m
- liquid nozzle de 400 mm
- dual-purpose nozzle - 270 mm
- round brush
- flat nozzle
- Padding nozzle
- Class M cartridge filter PTFE