



SPC 40 TE VEL DA DL

(Ref. 20601137)

Drilling metals, plastic materials and wood, with coolant
Usage très intensif

Guarantee:  **3** 

Photo et textes non contractuels

Product Information:

Slow down motion, automatic down motion (3 feed rates)
Electronic speed variator
Steel cast iron frame, head and stand
Steel column
Machined aluminium pulleys
Transmission through V belts with rapid adjustment of tension
Spindle fitted on bearings
Adjustable spindle rack motion through return spring
24V very low voltage controls :
- ON/OFF
- Switching on lamp
- Emergency Stop through mushroom stop button
- 3-point locking circuit breaker
Detachable servo protective shield
24V lighting
Electrical protection IP54
Noise level 50 dB
3-position reversible vice table (with vernier), V jaws to drill tubes
Vice fitted on guideways to center the part to drill
Rack-driven table, greisseur de la vis sans fin

Technical characteristics:

Height (cm) : 185.00
Width (cm) : 47.50
Length (cm) : 90.00
Net weight (Kg) : 400.00
Power(kW)
Power (V) 3-phase 400V
Spindle speed (rpm)
Max. drilling capacity (mm)
Morse taper MT4
Column dia (mm)
Spindle stroke (mm)
Number of gears
d: spindle/column distance (mm)
e: spindle/base distance (mm) 1 150
f: spindle/table distance (mm)
Table dimension (mm)
Distance between table grooves (mm)
Lighting Yes
Servo screen Yes
Reversible vice table Yes
Jaw width (mm)

Hot weather adaptation on request
Can be modified to 230V three-phase on request
Machined aluminium pulleys

Jaw height (mm)
Opening (mm)
Automatic down motion (mm/tr) 0.06 - 0.12 - 0.25
Slow down motion Yes
Semi automatic tapping No
Cross motion table No

Supplied with Self-clamping chuck and Chuck shank