



## SPC 40 TC VEL DA DL

(Ref. 20601142)

Drilling metals, plastic materials and wood, with coolant  
**Usage très intensif**

Guarantee:  **3** 

Photo et textes non contractuels

### Product Information:

Cross move table, Electronic speed variator, Slow down motion, automatic down motion (3 feed rates)  
Steel cast iron frame, head and stand  
Steel column  
Machined aluminium pulleys  
Transmission through V belts with rapid adjustment of tension  
Spindle fitted on bearings

Adjustable spindle rack motion through return spring  
24V very low voltage controls :  
- ON/OFF  
- Switching on lamp  
- Emergency Stop through mushroom stop button  
- 3-point locking circuit breaker  
Detachable servo protective shield  
24V lighting  
Electrical protection IP54  
Noise level 50 dB  
Rack-driven table, greaser for the screw without end  
Hot weather adaptation on request  
Can be modified to 230V three-phase on request  
Machined aluminium pulleys

### Technical characteristics:

Height (cm) : 185.00  
Width (cm) : 47.50  
Length (cm) : 90.00  
Net weight (Kg) : 600.00  
Power(kW)  
Power (V) 3-phase 400V  
Spindle speed (rpm)  
Max. drilling capacity (mm)  
Milling capacity (mm)  
Morse taper MT4  
Column dia (mm)  
Spindle stroke (mm)  
Number of gears  
d: spindle/column distance (mm)  
e: spindle/base distance (mm) 1 150  
f: spindle/table distance (mm)  
Table dimension (mm)  
Distance between table grooves (mm)  
Lighting Yes  
Servo screen Yes  
Reversible vice table No  
Coolant Yes  
Transversal / longitudinal stroke (mm)  
Automatic down motion (mm/tr) 0.06 - 0.12 - 0.25  
Slow down motion Yes  
Semi automatic tapping No  
Cross motion table Yes

**Supplied with Self-clamping chuck and Chuck shank**