



## SPC 32 TC VEL DL

(Ref. 20601131)

Drilling metals, plastic materials and wood, with coolant  
**Usage très intensif**

Guarantee:  **3** 

Photo et textes non contractuels

### Product Information:

- Cross move table,
- Slow down motion
- Electronic speed variator
- Steel cast iron frame, head and stand
- Steel column
- Machined aluminium pulleys
- Transmission through V belts with rapid adujstment of tension
- Spindle fitted on bearings
- Adjustable spindle mack motion through return spring
- 24V very low voltage controls :
  - ON/OFF
  - Switching on lamp
  - Emergency Stop through mushroom stay put button
  - 3-point locking circuit breaker
- Detachable servo protective shield
- 24V lighting
- Electrical protection IP54
- Noise level 50 dB
- Rack-driven table, graisseur de la vis sans fin
- Hot weather adaptation on request

### Technical characteristics:

- Height (cm) : 180.00
- Width (cm) : 43.50
- Length (cm) : 88.00
- Net weight (Kg) : 350.00
- Power(kW)
- Power (V) 3-phase 400V
- Spindle speed (rpm)
- Max. drilling capacity (mm)
- Milling capacity (mm)
- Morse taper MT3
- Column dia (mm)
- Spindle stroke (mm)
- Number of gears
- d: spindle/column distance (mm)
- e: spindle/base distance (mm) 1 210
- f: spindle/table distance (mm)
- Table dimension (mm)
- Distance between table grooves (mm)
- Lighting Yes
- Servo screen Yes

Can be modified to 230V three-phase on request  
Machined aluminium pulleys

Transversal / longitudinal stroke (mm)  
Automatic down motion (mm/tr) No  
Slow down motion Yes  
Semi automatic tapping No  
Cross motion table Yes

**Supplied with Self-clamping chuck and Chuck shank**